



**2016** 产品手册  
全钢载重子午线轮胎  
ALL steel Heavy Radial Tyre Series >>>>





山东华盛橡胶有限公司是一家以轮胎生产为主的企业，现有员工4500余人，公司成立于1995年，占地面积五十五万平方米，主要制造设备引自世界领先水平的日本、美国、德国和意大利。技术性能优越、匹配水平高。

公司产品已通过ISO9000国际质量管理体系认证和国家强制性产品认证（CCC）、ISO/TS 16949:2009认证、沙特SASOBGCC认证及巴西INNMETRO认证；技术指标达到美国DOT标准和欧盟ECE标准。

公司大力推进技术创新、营销创新、管理创新、服务创新和文化创新，着力打造精品轮胎，努力建设国内一流、世界知名的轮胎品牌。

Shandong Huasheng Rubber Co., Ltd. is professionally engaged in tyre production. The company was established in 1995, occupying an area of 550,000 square meters, and has employed over 4500 staff. The company main manufacturing equipments are introduced from Japan, American Germany and Italy, which possess the leading level of the world.

Our production has passed the qualification of ISO9000, the CCC of our nation, the ISO/TS 16949:2009,the SASOBGCC of Saudi Arabia and the INNMETRO of Brazil, besides that,the technical indicators of our company has reached the DOT Standard of American and the ECE Standard of European Union.

Shandong Huasheng Rubber Co.,Ltd engages in innovation of technology, marketing, management, service, and enterprise culture to manufacture high performance tyre and aiming to become a prominent player both in the nation and the world.





# 产品目录 PRODUCT CONTENTS

H5205 H5219 H5208 H5207 H5217 H5101 H5102



H5166 H5301 H5302 H5303 H5258 H5259 H5918+ H5765



H5203 H5928 H5268 H5218K H5216 H5918 H5108



H5978+ H5725 H5715 H5718 H5938+ H5958+ H5968+ H5735+



H5228 H518 H5206 H5201 H5202 H5801Q H5106 H5209



H5755+ H5978 H5105 H5107 H5218 H5716 H5109 H5103







**H5205**

**花纹特点:** 优化的胎面设计, 超强的耐磨性能和抗偏磨性能。滚动阻力低, 节省油耗 操控稳定性好。  
**合适状况:** 拖车轮长途运输。 高速公路等优质路面上使用。

**Pattern characteristic:**

Improved tread design, High wear resistance and eccentric wear resistance. Low rolling resistance, Save fuel consumption, good handling quality.

**Suitable conditions:**

Trailer tyre suitable for Long-distance transportation, running on high-grade road .

| 规格Size      | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|-------------|------|----------------------|---------------------------------------|-------------------------|---------------------------|--------------------|-----------------------|
| 11R22.5     | 16   | 8.25                 | 146/143M                              | 1050                    | 279                       | 3000/2750          | 830                   |
| 11R24.5     | 16   | 8.25                 | 149/146L                              | 1104                    | 279                       | 3250/3000          | 830                   |
| 205/75R17.5 | 14   | 6.00                 | 124/122M                              | 753                     | 204                       | 1600/1500          | 750                   |
| 215/75R17.5 | 14   | 6.00                 | 126/124M                              | 767                     | 211                       | 1650/1500          | 760                   |
| 225/70R19.5 | 14   | 6.75                 | 128/126M                              | 811                     | 226                       | 1800/1700          | 760                   |
| 235/75R17.5 | 16   | 6.75                 | 132/129M                              | 797                     | 233                       | 2000/1850          | 830                   |
| 245/70R19.5 | 16   | 7.50                 | 135/133M                              | 833                     | 248                       | 2180/2060          | 830                   |
| 255/70R22.5 | 16   | 7.50                 | 140/137M                              | 930                     | 255                       | 2500/2300          | 830                   |
| 265/70R19.5 | 16   | 7.50                 | 140/138M                              | 867                     | 262                       | 2500/2360          | 830                   |
| 275/70R22.5 | 16   | 8.25                 | 148/145M                              | 958                     | 276                       | 3150/2900          | 900                   |
| 285/75R24.5 | 16   | 8.25                 | 147/144L(m+s)                         | 1050                    | 283                       | 3070/2800          | 830                   |
| 295/75R22.5 | 16   | 9.00                 | 146/143L (m+s)                        | 1014                    | 298                       | 3000/2725          | 830                   |



**H5219**

**花纹特点:** 高耐磨, 高性价比。具有良好的抗侧滑及抗湿滑性能, 操控稳定性好。  
**合适状况:** 轻型货车 客车全轮位使用。 高速公路 一二级公路。

**Pattern characteristic:**

High wear resistance, High cost performance. Excellent anti-side-skid character and good drainage character, good handling quality.

**Suitable conditions:**

Suitable for all position of buses and light trucks running on Highway and roads of common grades.

| 规格Size      | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|-------------|------|----------------------|---------------------------------------|-------------------------|---------------------------|--------------------|-----------------------|
| 11R22.5     | 14   | 8.25                 | 144/142M                              | 1050                    | 279                       | 2800/2650          | 830                   |
| 11R24.5     | 14   | 8.25                 | 146/143M                              | 1104                    | 279                       | 3000/2725          | 830                   |
| 285/75R24.5 | 14   | 8.25                 | 144/141M                              | 1050                    | 283                       | 2800/2575          | 830                   |
| 295/75R22.5 | 14   | 9.00                 | 144/141M                              | 1014                    | 298                       | 2800/2575          | 830                   |



**H5208**

**花纹特点:** 宽胎面设计, 驱动性能和抓着力更强, 轮胎受力更均匀, 耐磨性更好。花纹底部采用防夹石子设计, 防花纹沟裂。

**合适状况:** 轻型、重型卡车和公共汽车全轮位。 较好, 较恶路面兼用

**Pattern characteristic:**

Widen tread width design provides excellent driving and gripping power. Extra deep tread provides an extra powerful traction and a long tread life. Closed shoulder maintains a good irregular wear resistance. With excellent crack and tear resistance character.

**Suitable conditions:**

Suitable for Light, heavy duty and bus all position on good or non-paved road.

| 规格Size      | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷Kg<br>Load | 对应充气压<br>Kpa/Pressure |
|-------------|------|----------------------|---------------------------------------|-------------------------|---------------------------|-------------------|-----------------------|
| 11R22.5     | 16   | 8.25                 | 146/143M                              | 1050                    | 279                       | 3000/2725         | 830                   |
| 11R24.5     | 16   | 8.25                 | 149/146L(m+s)                         | 1104                    | 279                       | 3250/3000         | 830                   |
| 285/75R24.5 | 16   | 8.25                 | 147/144L(m+s)                         | 1050                    | 283                       | 3070/2800         | 830                   |
| 295/75R22.5 | 16   | 9.00                 | 146/143L(m+s)                         | 1014                    | 298                       | 3000/2725         | 830                   |



**H5207**

**花纹特点:** 采用低生热过渡胶料保证轮胎高速性能, 使用耐磨、抗切割的胎面胶料配方, 加强的胎圈耐久结构, 保证轮胎耐久性能。

**合适状况:** 轻型货车 客车全轮位使用。 高速公路 一二级公路。

**Pattern characteristic:**

Suitable for highway and good quality road condition drive wheel, trailer wheel suitable for common or poor road surface, such as country road with anti-crack character, good abrasion resistance, anti-puncture character, excellent traction performance and loading character deepened & widened pattern of groove design, increase the traveled range and improve the adaptability to bad roads steering wheel , trailer wheel.

**Suitable conditions:**

Suitable for all position of buses and light trucks running on Highway and roads of common grades.

| 规格Size  | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|---------|------|----------------------|---------------------------------------|-------------------------|---------------------------|--------------------|-----------------------|
| 11R22.5 | 16   | 8.25                 | 146/143M                              | 1050                    | 279                       | 3000/2725          | 830                   |
| 11R24.5 | 16   | 8.25                 | 149/146L(m+s)                         | 1104                    | 279                       | 3250/3000          | 830                   |



**H5217**

**花纹特点:** 高耐磨, 高性价比。驱动及制动性能优越。

**合适状况:** 轻型货车 客车全轮位使用。 高速公路 一二级公路。

**Pattern characteristic:**

High wear resistance, High cost performance. Excellent traction performance and brake performance.

**Suitable conditions:**

Suitable for all position of buses and light trucks running on Highway and roads of common grades.

| 规格Size  | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷Kg<br>Load | 对应充气压<br>Kpa/Pressure |
|---------|------|----------------------|---------------------------------------|-------------------------|---------------------------|-------------------|-----------------------|
| 11R22.5 | 16   | 8.25                 | 146/143M                              | 1050                    | 279                       | 3000/2725         | 830                   |
| 11R24.5 | 16   | 8.25                 | 149/146L(m+s)                         | 1104                    | 279                       | 3250/3000         | 830                   |





**花纹特点:** 特殊胎面配方设计, 抗撕裂, 耐磨耗。封闭的胎肩设计, 均衡耐磨, 噪音小。高速行驶稳定性强, 滚动阻力小, 油耗低。  
**合适状况:** 导向或全轮位。 高速和良好路面的中长途卡车或客车适用。

**Pattern characteristic:**  
Specially recipe design provides tear resistance, high wear resistance, and excellent load capacity, Low rolling resistance & noise emission, excellent heat radiation, guiding stability. Excellent fuel efficiency.  
**Suitable conditions:**  
Suitable for steer or all wheel position of bus and truck running on high-grade road.

**HS101**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 11R22.5     | 16   | 8.25             | 146/143M                          | 1050                | 279                   | 3000/2725      | 830               |
| 12R22.5     | 18   | 9.00             | 152/149M                          | 1084                | 300                   | 3550/3250      | 930               |
| 315/80R22.5 | 20   | 9.00             | 157/153L                          | 1076                | 312                   | 4125/3650      | 870               |
| 295/80R22.5 | 18   | 9.00             | 152/149M                          | 1044                | 298                   | 3550/3250      | 900               |



**花纹特点:** 混合型花纹设计, 驱动、制动性优越。加长的花纹块设计, 可有效增强耐偏磨、耐异磨性能。花纹块之间的加强筋和排石结构设计, 防止崩花掉块和异物嵌入。  
**合适状况:** 货车拖车轮和驱动轮, 不适用导向轮。 一般铺装路面, 混合路面, 中短途使用。

**Pattern characteristic:**  
Mixed pattern design provide strong traction and breaking power. Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs.  
**Suitable conditions:**  
Suitable for trailer and driving wheel position, no suitable for steer position of short/middle distance trucks running on good road condition.

**HS102**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 315/80R22.5 | 20   | 9.00             | 157/153L                          | 1076                | 312                   | 4125/3650      | 870               |



**花纹特点:** 独特的带束层结构, 高耐磨低生热的胎冠配方; 行驶里程高, 牵引性好, 操纵性好; 节省能源, 高速性能优越; 优化和加强的胎圈设计; 特别适合特殊使用条件的要求; 子午线构造的胎体, 乘坐舒适; 减少车辆机件损耗。  
**合适状况:** 各种中、短途货车的全轮位。 国道、城乡、工地等混合路面和沙土路面。

**Pattern characteristic:**  
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.  
**Suitable conditions:**  
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

**HS203**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 315/80R22.5 | 20   | 9.0              | 157/153L                          | 1076                | 312                   | 4125/3650      | 870               |



**花纹特点:** 优异的牵引和越野性能, 超强的地面附着性能, 耐磨性能, 有强载能力和胎面抗刺扎性能。  
**合适状况:** 货车全轮位。 较恶路面。

**Pattern characteristic:**  
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.  
**Suitable conditions:**  
Suitable for all position of trucks running on non-paved roads.

**HS928**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 9.5R17.5    | 18   | 6.75             | 143/141J                          | 842                 | 240                   | 2725/2575      | 875               |
| 215/75R17.5 | 14   | 6.00             | 126/124M                          | 767                 | 211                   | 1700/1600      | 700               |
| 225/70R19.5 | 14   | 6.75             | 128/126M                          | 811                 | 226                   | 1800/1700      | 760               |
| 235/75R17.5 | 16   | 6.75             | 132/129M                          | 797                 | 233                   | 2000/1850      | 830               |
| 265/70R19.5 | 16   | 7.50             | 140/138M                          | 867                 | 262                   | 2500/2360      | 830               |
| 275/70R22.5 | 18   | 8.25             | 148/145M                          | 958                 | 276                   | 3150/2900      | 900               |
| 295/75R22.5 | 16   | 9.00             | 146/143L (m+s)                    | 1014                | 298                   | 3000/2725      | 830               |
| 315/80R22.5 | 20   | 9.00             | 156/150K(M+S)                     | 1076                | 312                   | 4000/3350      | 830               |



**花纹特点:** 独特的带束层结构, 高耐磨低生热的胎冠配方; 行驶里程高, 牵引性好, 操纵性好; 节省能源, 高速性能优越; 优化和加强的胎圈设计; 特别适合特殊使用条件的要求; 子午线构造的胎体, 乘坐舒适; 减少车辆机件损耗。  
**合适状况:** 各种中、短途货车的全轮位。 国道、城乡、工地等混合路面和沙土路面。

**Pattern characteristic:**  
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.  
**Suitable conditions:**  
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

**HS268**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 6.50R16LT   | 12   | 5.50F            | 110/105K                          | 750                 | 185                   | 1060/925       | 670               |
| 7.00R16LT   | 14   | 5.50F            | 118/114K                          | 775                 | 205                   | 1320/1180      | 770               |
| 7.50R16LT   | 14   | 6.00G            | 122/118L                          | 805                 | 215                   | 1500/1320      | 770               |
| 8.25R16LT   | 16   | 6.50H            | 128/124L                          | 855                 | 235                   | 1800/1600      | 770               |
| 8.25R20     | 16   | 6.5              | 139/137K                          | 974                 | 236                   | 2430/2300      | 930               |
| 9.00R20     | 16   | 7.0              | 144/142K                          | 1018                | 258                   | 2800/2650      | 900               |
| 10.00R20    | 18   | 7.5              | 149/146K                          | 1052                | 275                   | 3250/3000      | 930               |
| 11.00R20    | 18   | 8.0              | 152/149K                          | 1082                | 296                   | 3550/3250      | 930               |
| 11R22.5     | 16   | 8.25             | 146/143M                          | 1050                | 279                   | 3000/2725      | 830               |
| 11R24.5     | 16   | 8.25             | 149/146L(m+s)                     | 1104                | 279                   | 3250/3000      | 830               |
| 12.00R20    | 20   | 8.5              | 156/153K                          | 1122                | 313                   | 4000/3650      | 900               |
| 12.00R24    | 20   | 8.5              | 160/157K                          | 1226                | 313                   | 4500/4125      | 900               |
| 12R22.5     | 18   | 9.00             | 152/149M                          | 1084                | 300                   | 3550/3250      | 930               |
| 13R22.5     | 18   | 9.75             | 154/151L                          | 1124                | 320                   | 3750/3450      | 830               |
| 315/80R22.5 | 18   | 9.00             | 154/151M                          | 1076                | 312                   | 3750/3450      | 830               |
| 315/80R22.5 | 20   | 9.00             | 157/153L                          | 1076                | 312                   | 4125/3650      | 870               |





**花纹特点:** 优异的牵引和越野性能,超强的地面附着性能,耐磨性能,有强载能力和胎面抗刺扎性能。  
**合适状况:** 货车全轮位。一般路况。

**Pattern characteristic:**

Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.

**Suitable conditions:**

Suitable for all position of trucks running on non-paved roads.

**H5218K**

| 规格Size   | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负<br>荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|------|----------------------|---------------------------------------|-------------------------|---------------------------|------------------------|-----------------------|
| 12.00R24 | 20   | 8.5                  | 160/157K                              | 1226                    | 313                       | 4500/4125              | 900                   |



**花纹特点:** 三道纵向花纹和曲折横向沟设计,具有优异的路面抓着性和防湿滑性能。特殊胎面设计,低生热,耐磨性能更优异。

**合适状况:** 全轮位。 高速公路,国道等铺装路况。

**Pattern characteristic:**

3 continuous ribs,and the circumferential grooves enhances superior adhesion properties of the ground, excellent wet skid resistance,special tread design,providing a low heating up, wear resistance.

**Suitable conditions:**

Suitabl for all wheel position, running on high way and The national highway.

**H5216**

| 规格Size   | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负<br>荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|------|----------------------|---------------------------------------|-------------------------|---------------------------|------------------------|-----------------------|
| 12.00R24 | 20   | 8.5                  | 160/157K                              | 1226                    | 313                       | 4500/4125              | 900                   |



**花纹特点:** 横向大块加深花纹设计,提供超强的驱动力。开放性沟槽设计,很好的自洁能力。尤其加强抗刺扎、抗撕裂性能。

**合适状况:** 坏恶路面为主的短途自卸车全轮位。 城乡,工地,沙石等坏恶路面。

**Pattern characteristic:**

Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

**Suitable conditions:**

Suitable for short mileage vehicles running on various of non-paved roads.

**H5918**

| 规格 Size  | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数 / 速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎 / 双胎负荷 Kg<br>Load | 对应充气压<br>Kpa/Pressure |
|----------|-------|----------------------|-----------------------------------------|-------------------------|---------------------------|----------------------|-----------------------|
| 12.00R24 | 20    | 8.5                  | 160/157K                                | 1226                    | 313                       | 4500/4125            | 900                   |
| 11.00R20 | 18    | 8.0                  | 152/149K                                | 1085                    | 296                       | 3550/3250            | 930                   |
| 12.00R20 | 20    | 8.5                  | 154/151K                                | 1122                    | 313                       | 3750/3450            | 830                   |
| 7.50R16  | 14    | 6.00G                | 122/118L                                | 805                     | 215                       | 1500/1320            | 770                   |
| 8.25R16  | 16    | 6.50H                | 128/124L                                | 855                     | 235                       | 1800/1600            | 770                   |



**花纹特点:** 轮胎结构采用超强结构,具有优异的承载能力,超耐磨和抗刺扎的胎面配方,适用于路况较差的道路,专用于中短途使用。

**合适状况:** 驱动轮。 良好路面也可用于一般路面和恶劣路面。

**Pattern characteristic:**

Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.

**Suitable conditions:**

Suitable for driving wheel position on good road condition and non-paved roads.

**H5108**

| 规格Size   | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负<br>荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|------|----------------------|---------------------------------------|-------------------------|---------------------------|------------------------|-----------------------|
| 12.00R24 | 20   | 8.5                  | 160/157K                              | 1226                    | 313                       | 4500/4125              | 900                   |



**花纹特点:** 轮胎结构采用超强结构,具有优异的承载能力,超耐磨和抗刺扎的胎面配方,适用于路况较差的道路,专用于中短途使用。

**合适状况:** 驱动轮位。 多用于良好路面也可用于一般路面和恶劣的路面。

**Pattern characteristic:**

Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.

**Suitable conditions:**

Suitable for driving wheel position on good road condition and non-paved roads.

**H5228**

| 规格Size   | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负<br>荷<br>Kg Load | 对应充气压Kpa/<br>Pressure |
|----------|------|----------------------|---------------------------------------|-------------------------|---------------------------|------------------------|-----------------------|
| 12.00R24 | 20   | 8.5                  | 160/157K                              | 1226                    | 313                       | 4500/4125              | 900                   |



**花纹特点:** 轮胎结构采用超强结构,具有优异的承载能力,超耐磨和抗刺扎的胎面配方,适用于路况较差的道路,专用于中短途使用。

**合适状况:** 驱动轮位。 多用于良好路面也可用于一般路面和恶劣的路面。

**Pattern characteristic:**

Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.

**Suitable conditions:**

Suitable for driving wheel position on good road condition and non-paved roads.

**H518**

| 规格Size   | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负<br>荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|------|----------------------|---------------------------------------|-------------------------|---------------------------|------------------------|-----------------------|
| 12.00R24 | 20   | 8.5                  | 160/157K                              | 1226                    | 313                       | 4500/4125              | 900                   |





**花纹特点:** 高耐磨, 高性价比。

**合适状况:** 轻型货车 客车全轮位使用。 高速公路 一二级公路。

**Pattern characteristic:**

High wear resistance, High cost performance.

**Suitable conditions:**

Suitable for all position of buses and light trucks running on Highway and roads of common grades.

**H5206**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 7.50R16  | 14    | 6.00G             | 122/118L                             | 805                  | 215                    | 1500/1320         | 770                |
| 9.5R17.5 | 18    | 6.75              | 143/141M                             | 974                  | 229                    | 2725/2575         | 127PSI             |



**花纹特点:** 中长途好路用。优秀的载重性能。之字形沟槽提供优异的牵引和防侧滑能力。

**合适状况:** 全轮位。 城乡、国道、高速公路等铺装路面。

**Pattern characteristic:**

Suitable for medium/long-haul vehicles Running on high-grade road, excellent load capacity, straight shallow grooves offers an excellent drive, straight ride and anti-sidewall scuffing performance.

**Suitable conditions:**

Suitable for all wheel position, Running on the nation highway and high way.

**H5201**

| 规格 Size     | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|-------------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 315/70R22.5 | 20    | 9.00              | 157/153L                           | 1076                 | 312                    | 4125/3650       | 870                |



**花纹特点:** 混合型花纹设计, 提供优异的驱动、制动性能。加长的花纹块设计, 可有效增强耐偏磨、耐异磨性能。花纹块之间的加强筋和排石结构设计, 防止崩花掉块和异物嵌入。开放式胎肩设计, 增强散热性能。

**合适状况:** 驱动轮。 极好路面, 良好路面。

**Pattern characteristic:**

Mixed pattern design provide strong traction and breaking power, Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs on the blocks assure a firm grip and a powerful tr

**Suitable conditions:**

Suitable for driving wheel position on good road condition.

**H5202**

| 规格 Size     | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|-------------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 315/70R22.5 | 20    | 9.00              | 157/153L                           | 1076                 | 312                    | 4125/3650       | 870                |
| 295/80R22.5 | 18    | 9.00              | 152/149M                           | 1044                 | 298                    | 3550/3250       | 900                |



**花纹特点:** 独特的带束层结构, 高耐磨低生热的胎冠配方; 行驶里程高, 牵引性好, 操纵性好; 节省能源, 高速性能优越; 优化和加强的胎圈设计; 特别适合特殊使用条件的要求; 子午线构造的胎体, 乘坐舒适; 减少车辆机件损耗。

**合适状况:** 各种中、短途货车的全轮位。 国道、城乡、工地等混合路面和沙土路面。

**Pattern characteristic:**

Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.

**Suitable conditions:**

Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

**H5166**

| 规格 Size     | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|-------------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 385/65R22.5 | 20    | 11.75             | 160K                               | 1072                 | 389                    | 4500            | 900                |



**花纹特点:** 高速稳定性强, 超耐磨, 良好的载重能力。使用寿命长, 行驶里程高, 滞后损失小, 散热好。

**合适状况:** 卡车, 客车的拖车轮, 不适用导向轮和驱动轮良好的铺装路面与混合道路, 中长途车辆使用。

**Pattern characteristic:**

Excellent traction and draining performance, more original mileage.

**Suitable conditions:**

trailer tyre of bus and truck, not suitable for drive and steer wheel position running on well-paved roads and mixed pavements and medium/long-haul vehicles.

**H5106**

| 规格 Size     | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|-------------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 385/65R22.5 | 20    | 11.75             | 160K                               | 1072                 | 389                    | 4500            | 900                |



**花纹特点:** 独特的带束层结构, 高耐磨低生热的胎冠配方; 行驶里程高, 牵引性好, 操纵性好; 节省能源, 高速性能优越; 优化和加强的胎圈设计; 特别适合特殊使用条件的要求; 子午线构造的胎体, 乘坐舒适; 减少车辆机件损耗。

**合适状况:** 各种中、短途货车的全轮位。 国道、城乡、工地等混合路面和沙土路面。

**Pattern characteristic:**

Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.

**Suitable conditions:**

Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

**H5209**

| 规格 Size     | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|-------------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 385/65R22.5 | 20    | 11.75             | 160K                               | 1072                 | 389                    | 4500            | 900                |





**花纹特点:**独特的带束层结构,高耐磨低生热的胎冠配方。具有较强的抓着性和抗湿滑性能。优化和加强的胎圈设计,特别适合特殊使用条件的要求。子午线构造的胎体,乘坐舒适;减少车辆机件损耗。

**合适状况:**货车驱动轮。山地,矿山及一般路面。

**Pattern characteristic:**

Unique belt structure, with high wear-resistance and low producing heat crown formulation. Has a strong grip and wet-slip resistance performance. Optimized and enhanced bead design, especially for special conditions. Radial structure of the carcass, ma.

**Suitable conditions:**

Truck drive tyre, suitable for low speed ride on bad or common road, such as mine road, mountain road.

**H5801Q**

| 规格Size   | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|----------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 10.00R20 | 18   | 7.5              | 149/146K                          | 1052                | 275                   | 3250/3000      | 930               |
| 11.00R20 | 18   | 8.0              | 152/149K                          | 1082                | 296                   | 3550/3250      | 930               |
| 12.00R20 | 20   | 8.5              | 156/153K                          | 1122                | 313                   | 4000/3650      | 900               |
| 13R22.5  | 18   | 9.75             | 154/151L                          | 1124                | 320                   | 3750/3450      | 850               |



**花纹特点:**轮胎结构采用超强结构,具有优异的承载能力,超耐磨和抗刺扎的胎面配方,适用于路况较差的道路,专用于中短途使用。

**合适状况:**全轮位。极好路面、良好路面。

**Pattern characteristic:**

Excellent load capacity and Super abrasion resistance,tear resistance, high wear resistance,suitable to vehicles on low grade road and medium/long-haul vehicles.

**Suitable conditions:**

All wheel position. high-grade road.

**H5301**

| 规格 Size | 层级PR | 标准轮辋Standard Rim | 负荷指数 / 速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎 / 双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|---------|------|------------------|-------------------------------------|---------------------|-----------------------|------------------|-------------------|
| 12R22.5 | 18   | 9.0              | 152/149M                            | 1084                | 300                   | 3550/3275        | 930               |



**花纹特点:**大块肩部花纹设计,轮胎有良好的驱动性能。横向花纹和中部纵向花纹设计,兼具优异的直线行驶性能和制动性能。开放式宽沟和胎肩钢片设计,赋予轮胎良好的自洁和散热性能。

**合适状况:**货车驱动轮位。矿山、山地路面使用。

**Pattern characteristic:**

Large shoulder pattern design, has good driving performance of tire. Lateral pattern and central longitudinal pattern design, has excellent linear driving performance and braking performance. Design of open wide and shoulder steel sheet, self-cleaning and heat dissipation performance with good tires.

**Suitable conditions:**

Truck driving wheel. Mine, mountain road.

**H5302**

| 规格 Size | 层级PR | 标准轮辋Standard Rim | 负荷指数 / 速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎 / 双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|---------|------|------------------|-------------------------------------|---------------------|-----------------------|------------------|-------------------|
| 12R22.5 | 18   | 9.0              | 152/149M                            | 1084                | 300                   | 3550/3275        | 930               |



**花纹特点:**胎冠四条纵向花纹沟槽,提供优秀的操纵性能和高速性能。

**合适状况:**货车车辆的导向或拖车轮。良好及比较复杂的混合路面长、中、短途运输。

**Pattern characteristic:**

Four straight groove can provide excellent braking and driving performances.

**Suitable conditions:**

Suitable for steering wheel,trailer wheel,medium/long-haul vehicles,Running on good or common mixed pavements.

**H5303**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 295/80R22.5 | 18   | 9.00             | 152/149M                          | 1044                | 298                   | 3550/3250      | 900               |



**花纹特点:**胎冠四条纵向花纹沟槽,提供优秀的操纵性能和高速性能。

**合适状况:**货车车辆的导向或拖车轮。良好及比较复杂的混合路面长、中、短途运输。

**Pattern characteristic:**

Four straight groove can provide excellent braking and driving performances.

**Suitable conditions:**

Suitable for steering wheel,trailer wheel,medium/long-haul vehicles,Running on good or common mixed pavements.

**H5258**

| 规格Size      | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|-------------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 385/65R22.5 | 20   | 11.75            | 160K                              | 1072                | 389                   | 4500           | 900               |



**花纹特点:**胎冠四条纵向花纹沟槽,提供优秀的操作性能和高速性能。横向细小沟槽,可增加散热性能和在湿滑路面的抓地性能。肩部花纹沟设计,有效防止轮胎偏磨。

**合适状况:**导向轮和拖挂轮。中长途高速用,极好路面、良好路面。

**Pattern characteristic:**

4 straight groove can provide superior braking and driving performances,superior adhesion properties of the ground, excellent wet skid resistance,eccentric wear resistance.

**Suitable conditions:**

steer and trailer tyre,medium/long-haul vehicles,running on high-grade road.

**H5259**

| 规格Size   | 层级PR | 标准轮辋Standard Rim | 负荷指数/速度级别Load Index& speed Rating | 外直径 (mm)Overall Dia | 断面宽 (mm)Section Width | 单胎/双胎负荷Kg Load | 对应充气压Kpa/Pressure |
|----------|------|------------------|-----------------------------------|---------------------|-----------------------|----------------|-------------------|
| 11.00R20 | 18   | 8.0              | 152/149K                          | 1082                | 296                   | 3550/3250      | 930               |





**花纹特点:**独特的带束层结构,高耐磨,具有良好的冲击力,优化和加强的胎圈设计,具有良好的牵引性能,适用于高速公路,城市道路和普通公路。  
**合适状况:**货车驱动轮。 适用于高速公路,城市道路和普通公路。

**Pattern characteristic:**  
Tough belt construction, with high wear resistance and good impact force, Reinforced bead provide good traction.  
**Suitable conditions:**  
Suitable for driving wheel position of short/middle distance trucks on good road conditions .

**H5918+**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 10.00R20 | 18    | 7.5               | 149/146K                             | 1052                 | 275                    | 3250/3000         | 930                |



**花纹特点:**横向花纹为主体中间辅以加强筋设计,特殊的配方设计,耐刺扎、不易掉块。加强的胎体和胎体钢丝特殊镀层设计,赋予轮胎更强的承载能力。开放型的花纹沟和花纹沟防石子嵌入设计,轮胎有极佳的自洁性。  
**合适状况:**工矿专用轮胎,适用于矿区、工地等的碎石路面矿区、工地的短途自卸车、搅拌机等的驱动轮位。

**Pattern characteristic:**  
Transverse pattern as the main body of the middle of the reinforcement design, special formula design, resistant to thorn, not easy to block. Carcass and carcass ply steel special coating designed to strengthen the capacity of giving the tire stronger. The open pattern ditch and the pattern ditch prevent the stone to embed the design, the tire has the extremely good self - clean.  
**Suitable conditions:**  
Mining special tires, applicable to in mines, construction sites, such as gravel mining area, site of short self unloading, mixing car driving wheel.

**H5765**

矿山型

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149K                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 154/151K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:**全天候花纹设计,具有优异的牵引性能。增强型胎圈的圈部设计,具有较好的耐超载性能。加强的胎体及抗高冲击带束层设计,轮胎可经多次翻新使用。  
**合适状况:**中短途卡车、自卸车、搅拌机、牵引车的驱动轮位。国道、城乡、工地等混合路面。

**Pattern characteristic:**  
All weather pattern design, with excellent traction performance. Reinforced bead ring design, with better resistance to overload. To strengthen the body and high impact resistance belt design, can be repeated use of refurbished tires.  
**Suitable conditions:**  
Short haul trucks, dump truck, mixer truck, tractor driving wheel. National highway, urban and rural areas, construction sites and other mixed roads.

**H5978+**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149K                             | 1085                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 154/151K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:**专为无路或苛刻坏路面设计的矿山花纹轮胎、宽胎冠、深花纹提供更高的行驶里程。横向大花 纹块能产生强劲的驱动力,在干湿路面均能保持优良抓地性能,超载能力、耐刺扎性能和越野 性能尤为突出。  
**合适状况:**货车驱动轮位。 矿山、山地路面使用。

**Pattern characteristic:**  
Special designed mine pattern tyre for harsh road ,with wide tyre crown and deep tread, which could provide higher mileage.The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavem.  
**Suitable conditions:**  
Truck drive tyre, use for Mining/Mountain road.

**H5725**

矿山型

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 4000/3650         | 900                |



**花纹特点:**横向大块加深花纹设计,提供超强的驱动性能。开放型沟槽设计有很好自洁能力。尤其加强了 胎体强度设计,提供更强的承载能力。尤其加强抗刺扎、抗撕裂性能,耐磨耗,耐偏磨。  
**合适状况:**超重载、恶劣路面的短途自卸车驱动轮位或全轮位。工地、矿山、泥泞等严重恶劣路况。

**Pattern characteristic:**  
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.  
**Suitable conditions:**  
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

**H5715**

矿山型

| 规格Size   | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压Kpa/ Pressure |
|----------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 9.00R20  | 16    | 7.0               | 144/142K                           | 1018                 | 258                    | 2800/2650       | 900                |
| 10.00R20 | 18    | 7.5               | 149/146K                           | 1052                 | 275                    | 3250/3000       | 930                |
| 11.00R20 | 18    | 8.0               | 152/149K                           | 1082                 | 296                    | 3550/3250       | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                           | 1122                 | 313                    | 4000/3650       | 900                |



**花纹特点:**轮胎结构采用超强结构,具有优异的承载能力,超耐磨和抗刺扎的胎面配方,适用于路况较差的道路,专用于中、短途使用。  
**合适状况:**轮位。 一般路面、较差路面。

**Pattern characteristic:**  
Tire adopt super structure, with excellent carrying capacity, super wear-resistant and anti-puncture tread formulation ,suitable for poor road condition, dedicated to the short-distance use.  
**Suitable conditions:**  
All-wheel position,Ordinary Road,bad road.

**H5718**

| 规格Size   | 层级 PR | 标准轮辋 Standard Rim | 负荷指数/速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎/双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|------------------------------------|----------------------|------------------------|-----------------|--------------------|
| 12.00R20 | 20    | 8.5               | 156/153K                           | 1122                 | 313                    | 4000/3650       | 900                |





**花纹特点:** 横向大块加深花纹设计, 提供超强的驱动力。开放性沟槽设计, 很好的自洁能力。尤其加强抗刺扎、抗撕裂性能。

**合适状况:** 坏恶路面为主的短途自卸车全轮位。 城乡, 工地, 沙石等坏恶路面。

**Pattern characteristic:**  
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

**Suitable conditions:**  
Suitable for short mileage vehicles running on various of non-paved roads.

**H5938+**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:** 横向大块加深花纹设计, 提供超强的驱动力。开放性沟槽设计, 很好的自洁能力。尤其加强抗刺扎、抗撕裂性能。

**合适状况:** 坏恶路面为主的短途自卸车全轮位。城乡, 工地, 沙石等坏恶路面。

**Pattern characteristic:**  
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

**Suitable conditions:**  
Suitable for short mileage vehicles running on various of non-paved roads.

**H5958+**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:** 横向大块加深花纹设计, 提供超强的驱动力。开放性沟槽设计, 很好的自洁能力。尤其加强抗刺扎、抗撕裂性能。

**合适状况:** 坏恶路面为主的短途自卸车全轮位。 城乡, 工地, 沙石等坏恶路面。

**Pattern characteristic:**  
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

**Suitable conditions:**  
Suitable for short mileage vehicles running on various of non-paved roads.

**H5968+**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:** 横向大块加深花纹设计, 提供超强的驱动力。开放性沟槽设计有很好自洁能力。尤其加强了 胎体强度设计, 提供更强的承载能力。尤其加强抗刺扎、抗撕裂性能, 耐磨耗, 耐偏磨。

**合适状况:** 超重载、恶劣路面的短途自卸车驱动轮位或全轮位。 工地、矿山、泥泞等严重恶劣路况。

**Pattern characteristic:**  
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.

**Suitable conditions:**  
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

**H5735+ 矿山型**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:** 专为无路或苛刻坏路面设计的矿山花纹轮胎、宽胎冠、深花纹提供更高的行驶里程。横向大花 纹块能产生强劲的驱动力, 在干湿路面均能保持优良抓地性能, 超载能力、耐刺扎性能和越野 性能尤为突出。

**合适状况:** 货车驱动轮位。 矿山、山地路面使用。

**Pattern characteristic:**  
Special designed mine pattern tyre for harsh road ,with wide tyre crown and deep tread, which could provide higher mileage.The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavem.

**Suitable conditions:**  
Truck drive tyre, use for Mining/Mountain road.

**H5755+ 矿山型**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 11.00R20 | 18    | 8.0               | 152/149M                             | 1082                 | 296                    | 3550/3250         | 930                |
| 12.00R20 | 20    | 8.5               | 156/153K                             | 1122                 | 313                    | 3750/3450         | 830                |



**花纹特点:** 横向大块加深花纹设计, 提供超强的驱动力。开放性沟槽设计, 很好的自洁能力。尤其加强抗刺扎、抗撕裂性能。

**合适状况:** 坏恶路面为主的短途自卸车全轮位。 城乡, 工地, 沙石等坏恶路面。

**Pattern characteristic:**  
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

**Suitable conditions:**  
Suitable for short mileage vehicles running on various of non-paved roads.

**H5978**

| 规格 Size  | 层级 PR | 标准轮辋 Standard Rim | 负荷指数 / 速度级别 Load Index& speed Rating | 外直径 (mm) Overall Dia | 断面宽 (mm) Section Width | 单胎 / 双胎负荷 Kg Load | 对应充气压 Kpa/Pressure |
|----------|-------|-------------------|--------------------------------------|----------------------|------------------------|-------------------|--------------------|
| 10.00R20 | 18    | 7.5               | 149/146K                             | 1052                 | 275                    | 3250/3000         | 930                |





**花纹特点:** 细花纹沟设计有效提高抗湿滑性能和制动性能。独特的肩部小沟槽设计极大提高肩部的抗偏磨、异磨能力，纵向曲折花纹沟使轮胎具有优异的牵引性能和排水性能。  
**合适状况:** 货车全轮位。 高速公路，城市道路和普通公路。

**Pattern characteristic:**  
Superior braking and driving performances, excellent wet skid resistance and eccentric wear resistance, Straight groove design helps to provide Super-strong traction, and water drainage.  
**Suitable conditions:**  
All wheel position of truck. Running on highway, city road and Common roads.

**H5105**

| 规格 Size | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数 / 速度级别<br>Load Index& speed<br>Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎 / 双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|---------|-------|----------------------|--------------------------------------------|-------------------------|---------------------------|----------------------|-----------------------|
| 12R22.5 | 18    | 9.00                 | 152/149M                                   | 1084                    | 300                       | 3550/3250            | 930                   |



**花纹特点:** 高特殊胎面胶配方 耐磨性能好 行驶里程高。开放式胎肩设计 散热好。混合型花纹设计，牵引力和抓着力强，高速，高载优异的牵引，制动，防着性能。  
**合适状况:** 货车驱动轮位，好路或极好路面的中长途货车使用。

**Pattern characteristic:**  
Specially recipe design provides wear-resistance, low heat generation, Excellent traction and draining performance, more original mileage. Mix pattern supplies excellent traction performance, braking performance, supper driving and anti-wet ability.  
**Suitable conditions:**  
Stuitable for driving position, medium/long-haul vehicles, running on high-grade road.

**H5107**

| 规格 Size | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数 / 速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎 / 双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|---------|-------|----------------------|-----------------------------------------|-------------------------|---------------------------|----------------------|-----------------------|
| 12R22.5 | 18    | 9.00                 | 152/149M                                | 1084                    | 300                       | 3550/3250            | 930                   |
| 13R22.5 | 18    | 9.75                 | 154/151L                                | 1124                    | 320                       | 3750/3450            | 830                   |



**花纹特点:** 轮胎结构采用超强结构，具有优异的承载能力，超耐磨和抗刺扎的胎面配方，适用于路况较差的道路，专用于中短途使用。  
**合适状况:** 全轮位。 一般路况。

**Pattern characteristic:**  
Excellent load capacity and Super abrasion resistance, tear resistance, high wear resistance, suitable to vehicles on low grade road and medium/long-haul vehicles.  
**Suitable conditions:**  
All wheel position. Common road condition.

**H5218**

| 规格Size   | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|-------|----------------------|---------------------------------------|-------------------------|---------------------------|--------------------|-----------------------|
| 9.00R20  | 16    | 7.0                  | 144/142K                              | 1018                    | 258                       | 2800/2650          | 900                   |
| 10.00R20 | 18    | 7.5                  | 149/146K                              | 1052                    | 275                       | 3250/3000          | 930                   |
| 11.00R20 | 18    | 8.0                  | 152/149K                              | 1082                    | 296                       | 3550/3250          | 930                   |
| 12.00R20 | 20    | 8.5                  | 156/153K                              | 1122                    | 313                       | 4000/3650          | 900                   |



**花纹特点:** 轮胎结构采用超强结构，具有优异的承载能力，超耐磨和抗刺扎的胎面配方，适用于路况较差的道路，专用于中短途使用。  
**合适状况:** 全轮位。 极好路面、良好路面。

**Pattern characteristic:**  
Excellent load capacity and Super abrasion resistance, tear resistance, high wear resistance, suitable to vehicles on low grade road and medium/long-haul vehicles.  
**Suitable conditions:**  
All wheel position. high-grade road.

**H5716**

| 规格 Size  | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数 / 速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎 / 双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|----------|-------|----------------------|-----------------------------------------|-------------------------|---------------------------|----------------------|-----------------------|
| 11.00R20 | 18    | 8.0                  | 152/149K                                | 1085                    | 296                       | 3550/3250            | 930                   |
| 12R22.5  | 18    | 9.00                 | 152/149K                                | 1084                    | 300                       | 3550/3250            | 930                   |



**花纹特点:** 散热性以及直线行驶稳定性好，较强的操控性能。  
**合适状况:** 货车驱动轮位。中途拖车或导向轮位，高速公路及良好路面使用。

**Pattern characteristic:**  
Low heat generating, excellent high speed driving character, good handling quality.  
**Suitable conditions:**  
Suitable for driving wheel position. Steer and trailer wheel, suitable for high way and good quality road use.

**H5109**

| 规格Size      | 层级PR | 标准轮辋<br>Standard Rim | 负荷指数/速度级别<br>Load Index& speed<br>Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎/双胎负荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|-------------|------|----------------------|------------------------------------------|-------------------------|---------------------------|--------------------|-----------------------|
| 315/80R22.5 | 20   | 9.00                 | 157/153L                                 | 1076                    | 312                       | 4125/3650          | 870                   |



**花纹特点:** TMS 技术和特殊配方组合，抗耐磨性能更佳；特殊花纹设计理念，具有优秀的抗偏磨耗性。驱动力和操控性能更好。  
**合适状况:** 驱动轮。 好路或极好路面的中长途卡车使用。

**Pattern characteristic:**  
TMS technology and special compound for smooth tread wear. Special pattern design provides good anti eccentric wear . Block tread.  
**Suitable conditions:**  
Suitable for driving wheel position of middle/long distance trucks running on good road condition.

**H5103**

| 规格 Size     | 层级 PR | 标准轮辋<br>Standard Rim | 负荷指数 / 速度级别<br>Load Index& speed Rating | 外直径 (mm)<br>Overall Dia | 断面宽 (mm)<br>Section Width | 单胎 / 双胎负<br>荷<br>Kg Load | 对应充气压<br>Kpa/Pressure |
|-------------|-------|----------------------|-----------------------------------------|-------------------------|---------------------------|--------------------------|-----------------------|
| 11R22.5     | 16    | 8.25                 | 146/143M                                | 1050                    | 279                       | 3000/2725                | 830                   |
| 12R22.5     | 18    | 9.00                 | 152/149M                                | 1084                    | 300                       | 3550/3250                | 930                   |
| 295/80R22.5 | 18    | 9.00                 | 152/149M                                | 1044                    | 298                       | 3550/3250                | 900                   |





4.50-16 6.00-13 6.00-16 7.00-16 5.00-12 6.00-15 7.50-15 5.00-14 6.00-16 7.50-16  
5.00-16 6.50-14 8.25-16 5.50-13 6.50-15 7.00-15 7.00-20 7.50-20 8.25-20 9.00-20  
10.00-20 11.00-20 12.00-20

### 曲线花纹

滚动阻力小，防侧滑性能好，适于公路高速行驶，省燃油，节约能源，经济效益好。  
The tyres have small in rolling resistance and sideslip-preventing.They are suitable for driving in high speed and saving oil and beneficial.

**HS228**



4.00-16 4.50-16 5.00-14 5.00-16 5.50-16 6.50-15 6.50-14 6.50-16 7.00-16 8.25-16  
8.25-20 9.00-16 7.00-20 7.50-20 8.25-20 9.00-20 10.00-20 11.00-20 12.00-20  
7.50-16

### 八角花纹

高耐磨，超强载，自洁性好，适于沙石路和普通路面行驶。  
The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

**HS868**



4.00-16 4.50-16 5.00-14 5.00-16 5.50-16 6.50-15 6.50-14 6.50-16 7.00-16 8.25-16  
8.25-20 9.00-16 7.00-20 7.50-20 8.25-20 9.00-20 10.00-20 11.00-20 12.00-20  
7.50-16

### 八角花纹

高耐磨，超强载，自洁性好，适于沙石路和普通路面行驶。  
The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

**HS388**



11.00-20

### 蛇形花纹

高耐磨，超强载，自洁性好，适于沙石路和普通路面行驶。  
The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

**HS998**

|                         | 轮胎规格<br>Tyre Size | 层级<br>Ply Rating | 轮辋<br>Rim                       |                                                                          | 新胎充气外缘尺寸<br>Inflated Dimensions |                             | 最大负荷<br>Max Load |           | 相应气压<br>Inflation Pressure |
|-------------------------|-------------------|------------------|---------------------------------|--------------------------------------------------------------------------|---------------------------------|-----------------------------|------------------|-----------|----------------------------|
|                         |                   |                  | 标准轮辋<br>Standard rim            | 允许轮辋<br>Permitted rim                                                    | 断面宽(mm)<br>Section Width        | 外直径(mm)<br>Overall Diameter | Sinle Load       | Dual Load |                            |
| 轻卡胎<br>Light truck tyre | 4.00-8            | 4                | 3.00D                           | 2.50C                                                                    | 110                             | 425                         | 225              | -         | 300                        |
|                         | 4.00-12           | 4                | 3.00D                           | 2.50C                                                                    | 110                             | 535                         | 250              | -         | 340                        |
|                         | 4.00-14           | 4                | 3.00D                           | 2.50C                                                                    | 110                             | 590                         | 270              | -         | 340                        |
|                         | 4.50-14           | 8                | 3.00D                           | 3 <sup>1</sup> / <sub>2</sub>                                            | 122                             | 625                         | 570              | -         | 360                        |
|                         | 4.50-12uLT        | 4.6.8            | 3.00B                           | 3 <sup>1</sup> / <sub>2</sub> J 3.00D 3.50B                              | 127                             | 545                         | 415              | 395       | 400                        |
|                         | 4.50-16LT         | 6                | 3.00B                           | 3.00D 3.50D                                                              | 127                             | 665                         | 325              | -         | 250                        |
|                         | 5.00-12uLT        | 6.8              | 3.50B                           | 3.00D 3.00B 4J 3 <sup>1</sup> / <sub>2</sub> J 4.00B                     | 143                             | 568                         | 485              | 465       | 400                        |
|                         | 5.00-14LT         | 8                | 3.50                            | 3 <sup>1</sup> / <sub>2</sub> J 4.00B                                    | 143                             | 615                         | 340              | -         | 250                        |
|                         | 5.00-16LT         | 8                | 3.50                            | 3 <sup>1</sup> / <sub>2</sub> J 4.00B                                    | 145                             | 685                         | 375              | -         | 250                        |
|                         | 5.50-16LT         | 8                | 4.00                            | 4 <sup>1</sup> / <sub>2</sub> J                                          | 165                             | 705                         | 425              | -         | 250                        |
|                         | 550-13LT          | 6.8              | 4J                              | 4 <sup>1</sup> / <sub>2</sub> J 5J                                       | 160                             | 620                         | 565              | 500       | 420                        |
|                         | 6.00-14LT         | 6.8              |                                 | 4J5J                                                                     | 170                             | 680                         | 685              | 600       | 420                        |
|                         | 6.00-15LT         | 6.8              | 4.50E                           | 4 <sup>1</sup> / <sub>2</sub> K                                          | 170                             | 705                         | 720              | 630       | 420                        |
|                         | 6.00-16LT         | 6.8.10           | 4.50E                           | 4.00E                                                                    | 170                             | 730                         | 860              | 755       | 530                        |
|                         | *7.00-20          | 10.12.14         | 5.5                             | 5.50S 6.0 6.00S                                                          | 200                             | 904                         | 1580             | 1385      | 740                        |
|                         | 7.50-20           | 8.10.12.14       | 6.0                             | 6.00T 6.5 6.50T                                                          | 215                             | 935                         | 1885             | 1655      | 810                        |
|                         | *7.50-16LT        | 6.8.10.12.14     | 5.50F                           | 6.00G                                                                    | 200                             | 775                         | 1220             | 1075      | 630                        |
|                         | *11.00-20         | 12.14.16.18      | 8.0                             | 8.00V 8.5 8.5V5 <sup>0</sup> 8.50V                                       | 293                             | 1085                        | 3270             | 2870      | 810                        |
|                         | 12.00-20          | 16.18            | 8.5                             | 8.50V 8.50V5 <sup>0</sup> 9.00V                                          | 315                             | 1125                        | 3730             | 3270      | 810                        |
|                         | 6.00-13LT         | 6.8              |                                 | 4J5J                                                                     | 170                             | 655                         | 655              | 570       | 6./8.                      |
|                         | 6.00-14LT         | 6.8              |                                 | 4J5J                                                                     | 170                             | 680                         | 685              | 600       | 420                        |
|                         | 6.00-15LT         | 6.8              | 4.50E                           | 4 <sup>1</sup> / <sub>2</sub> K                                          | 170                             | 705                         | 720              | 630       | 420                        |
|                         | 6.00-16LT         | 6.8.10           | 4.50E                           | 4.00E                                                                    | 170                             | 730                         | 860              | 755       | 530                        |
|                         | 6.50-14LT         | 6.8              | 4 <sup>1</sup> / <sub>2</sub> J | 5J                                                                       | 180                             | 705                         | 785              | 690       | 420                        |
|                         | 6.50-15LT         | 6.8              | 4.50E                           | 4 <sup>1</sup> / <sub>2</sub> K 5K 5 <sup>1</sup> / <sub>2</sub> K 5.50F | 180                             | 730                         | 820              | 720       | 420                        |
|                         | *6.50-16LT        | 6.8.10.12        | 5.50F                           | 5.00E 5.50F                                                              | 185                             | 750                         | 975              | 860       | 530                        |
|                         | 7.00-15LT         | 6.8.10           | 5.50F                           | 6.00G                                                                    | 200                             | 750                         | 1040             | 915       | 530                        |
|                         | *7.00-16LT        | 6.8.10.12.14     | 5.50F                           | 6.00G                                                                    | 200                             | 775                         | 1220             | 1075      | 630                        |
|                         | 7.50-15LT         | 8.10.12          | 6.00G                           | 5.50F 6.50H                                                              | 215                             | 780                         | 1370             | 1210      | 630                        |
|                         | *7.50-16LT        | 6.8.10.12.14     | 6.00G                           | 5.50F 6.50H                                                              | 215                             | 805                         | 1405             | 1240      | 630                        |
|                         | *8.25-16LT        | 6.8.10.12.14.16  | 6.50H                           | 6.00G                                                                    | 235                             | 855                         | 1705             | 1500      | 630                        |
|                         | 9.00-16LT         | 6.8.10.12.14     | 6.50H                           | 6.00G 7.00H                                                              | 255                             | 890                         | 1955             | 1720      | 630                        |

|                          | 轮胎规格<br>Tyre Size | 层级<br>Ply Rating | 轮辋<br>Rim            |                            | 新胎充气外缘尺寸<br>Inflated Dimensions |                             | 最大负荷<br>Max Load |           | 相应气压<br>Inflation Pressure |
|--------------------------|-------------------|------------------|----------------------|----------------------------|---------------------------------|-----------------------------|------------------|-----------|----------------------------|
|                          |                   |                  | 标准轮辋<br>Standard rim | 允许轮辋<br>Permitted rim      | 断面宽(mm)<br>Section Width        | 外直径(mm)<br>Overall Diameter | Sinle Load       | Dual Load |                            |
| 载重胎<br>Off-the-load tyre | 7.00-20           | 10.12.14         | 5.5                  | 5.50S 6.0 6.00S            | 200                             | 904                         | 1580             | 1385      | 740                        |
|                          | 7.50-20           | 8.10.12.14       | 6.0                  | 6.00T 6.5 6.50T            | 215                             | 935                         | 1885             | 1655      | 810                        |
|                          | 8.25-20           | 10.12.14.16      | 6.5                  | 6.50T 7.0 7.00T 7.0T50     | 235                             | 974                         | 2205             | 1940      | 810                        |
|                          | 9.00-20           | 10.12.14.16      | 7.0                  | 7.00T 7.0T50 7.5 6.5 7.50V | 259                             | 1018                        | 2575             | 2255      | 770                        |
|                          | 10.00-20          | 12.14.16.18      | 7.5                  | 7.50V 8.0 8.00V 8.0V50     | 278                             | 1055                        | 3000             | 2630      | 810                        |
|                          | 11.00-20          | 12.14.16.18      | 8.0                  | 8.00V 8.5 8.5V50 8.50V     | 293                             | 1085                        | 3270             | 2870      | 810                        |
|                          | 12.00-20          | 16.18            | 8.5                  | 8.50V 8.50V50 9.00V        | 315                             | 1125                        | 3730             | 3270      | 810                        |
|                          | 10.00-20          | 12.14.16.18      | 7.5                  | 7.50V 8.0 8.00V 8.0V50     | 278                             | 1055                        | 3000             | 2630      | 810                        |
|                          | 11.00-20          | 12.14.16.18      | 8.0                  | 8.00V 8.5 8.5V50 8.50V     | 293                             | 1085                        | 3270             | 2870      | 810                        |
|                          | 12.00-20          | 16.18            | 8.5                  | 8.50V 8.50V50 9.00V        | 315                             | 1125                        | 3730             | 3270      | 810                        |
|                          |                   |                  |                      |                            |                                 |                             |                  |           |                            |





14.00-24 17.5-25 20.5-25 23.5-25 16.00-25 26.5-25 16/70-20 13.00-25 18.00-25 29.5-25 16/70-24

### 条形花纹

耐割切，耐磨耗，适合苛刻复杂的地形条件，使用寿命长。  
For the complex,variable and harsh conditions of use,the tyres have the different featrues of wearing resistance and wearing cutted,safe and reliable.

**HS668**



23.5-25

### 花纹

抓着力好，自洁力好，耐湿滑性强，适合各种路面和气候条件。  
The tyres have the features of good grasping force to ground,standing the sideslip-preventing,and the tyres are suitable for all kinds of conditions of road and climates.

**HS866**



23.5-25

### 花纹

抓着力好，自洁力好，牵引性能高，负荷力强，适合松软路面、沙石地等矿山作业环境。  
With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

**HS686**



6.50-16 7.00-16 7.50-16 8.25-16 9.00-20 10.00-20 11.00-20

### 矿山花纹

抓着力好，自洁力好，牵引性能高，负荷力强，适合松软路面、沙石地等矿山作业环境。  
With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

**HS118**

| 轮胎规格<br>Tyre Size | 层级<br>Ply Rating | 轮辋<br>Rim            |                       | 新胎充气外缘尺寸<br>Inflated Dimensions |                             | 最大负荷<br>Max Load |         |         | 相应气压<br>Inflation Pressure | 气门嘴型号<br>Valve Size |
|-------------------|------------------|----------------------|-----------------------|---------------------------------|-----------------------------|------------------|---------|---------|----------------------------|---------------------|
|                   |                  | 标准轮辋<br>Standard rim | 允许轮辋<br>Permitted rim | 断面宽(mm)<br>Section Width        | 外直径(mm)<br>Overall Diameter | 65 km/h          | 50 km/h | 15 km/h |                            |                     |
| 17.5-25           | 12               | 14.00/1.5            | —                     | 445                             | 1350                        | 3120             | 3750    | 4190    | 280                        | Z1-01-8             |
| 17.5-25           | 14               | 14.00/1.5            | —                     | 445                             | 1350                        | 3330             | 4010    | 4480    | 280                        | Z1-01-8             |
| 17.5-25           | 20               | 14.00/1.5            | —                     | 445                             | 1398                        | -                | -       | 5440    | 280                        | Z1-01-8             |
| 20.5-25           | 16               | 17.00/20             | —                     | 520                             | 1490                        | 4280             | 5170    | 5770    | 350                        | Z1-01-6             |
| 20.5-25           | 20               | 17.00/20             | —                     | 520                             | 1548                        | 4880             | 5900    | 6580    | 350                        | Z1-01-6             |
| 23.5-25           | 16               | 19.5/2.5             | —                     | 595                             | 1615                        | 5170             | 6250    | 6970    | 350                        | Z1-01-8             |
| 23.5-25           | 20               | 19.5/2.5             | —                     | 595                             | 1673                        | 5530             | 6680    | 7460    | 280                        | Z1-01-8             |
| 14.00-24          | 16/24            | 10.00                | —                     | 375                             | 1370                        | 4760/6030        |         |         | 420/630                    | Z1-01-8             |
| 16.00-25          | 20/28            | 11.25/2.0            | —                     | 430                             | 1546                        | 6220/7360        |         |         | 420/560                    | Z1-01-8             |
| 26.5-25           | 16/20            | 22.00/3.0            | —                     | 675                             | 1750                        | 11500/13200      |         |         | 275/350                    | Z1-01-8             |
| 16/70-20          | 10/14            | 13.00                | —                     | 410                             | 1075                        | 4200/5150        |         |         | 325/450                    | Z1-01-8             |
| 18.00-25          | 20/28            | 13.00/2.5            | —                     | 495                             | 1615                        | 7230/8810        |         |         | 350/490                    | Z1-01-8             |
| 29.5-25           | 16/22            | 25.00/3.5            | —                     | 750                             | 1875                        | 12900/15000      |         |         | 250/325                    | Z1-01-8             |
| 16/70-24          | 10/14            | 13.00                | —                     | 410                             | 1175                        | 4750/5650        |         |         | 325/4.50                   | Z1-01-8             |



5.00-8 6.00-9 6.50-10 7.00-9 7.00-12 28X9-15 8.25-12 8.25-15

### 叉车花纹

牵引性能好，负荷高，散热性能好，适合在复杂苛刻的地形条件下运输作业。  
The drawing quality is good and the tyres are high in loading and good warmtherasing.

**HS688**

| Industrial tyre、叉车胎 | 轮胎规格<br>Tyre Size | 层级<br>Ply Rating | 轮辋<br>Rim            |                       | 新胎充气外缘尺寸<br>Inflated Dimensions |                             | 最大负荷<br>Max Load |         |         |         | 相应气压<br>Inflation Pressure | 气门嘴型号<br>Valve Size |
|---------------------|-------------------|------------------|----------------------|-----------------------|---------------------------------|-----------------------------|------------------|---------|---------|---------|----------------------------|---------------------|
|                     |                   |                  | 标准轮辋<br>Standard rim | 允许轮辋<br>Permitted rim | 断面宽(mm)<br>Section Width        | 外直径(mm)<br>Overall Diameter | 10 km/h          | 25 km/h | 40 km/h | 50 km/h |                            |                     |
| Industrial tyre、叉车胎 | 5.00-8            | 8.10             | 3.50D                | 3.00D                 | 137                             | 470                         | 950              | 765     | 665     | 595     | 800                        | TZ1-45              |
|                     | 6.00-9            | 10               | 4.00E                | 4.50E                 | 160                             | 540                         | 1410             | 1135    | 985     | 885     | 850                        | TZ1-45              |
|                     | 6.50-10           | 10               | 5.00F                | 5.50F                 | 175                             | 590                         | 1545             | 1245    | 1080    | 970     | 775                        | TZ1-45              |
|                     | 7.00-9            | 10               | 5.00S                | -                     | 190                             | 590                         | 1865             | 1500    | 1300    | 1170    | 850                        | TZ1-45              |
|                     | 7.00-12           | 12               | 5.00S                | 5.50S                 | 190                             | 676                         | 2225             | 1790    | 1505    | 1400    | 850                        | TZ1-45              |
|                     | 28X9-15           | 12,14,16         | 7.0                  | 7.00T                 | 222                             | 710                         | 3515             | 2705    | 2180    | 1850    | 900                        | -                   |
|                     | 8.25-12           | 12               | 6.5                  | 5.00S                 | 235                             | 765                         | 2950             | 2375    | 2060    | 1855    | 750                        | TZ1-50              |
|                     | 8.25-15           | 14               | 6.5                  | 6.50T                 | 235                             | 840                         | 3230             | 2600    | 2255    | 2030    | 800                        | TZ1-50              |
|                     |                   |                  |                      |                       |                                 |                             |                  |         |         |         |                            |                     |





**同行 共赢新未来**  
THE NEW FUTURE TOGETHER AND WIN-WIN